



Only 02-06 Poles
have this stick point

5	Clamp	Copper Alloy	Sn Plated
4	Screw	Steel	M2/Zn Plated
3	Cage	Copper Alloy	M2/Ni Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0

UL 标准 / UL Standard:	B	C	D
额定电压/电流 / Rated Voltage(V)/Current(A)	300/8	/	300/8
EC 标准 / EC Standard:			
过压类别 / Overvoltage Category / 污染等级 / Pollution Degree	II/2		
额定电压/电流 / Rated Voltage(V)/Current(A)	250/7		
额定脉冲电压 (KV) / Rate Impulse Voltage (KV)	2.5		
扭矩 / Torque / Tightening (N·m/Lb.in)	M2: 0.2/1.77		
导线范围 (硬线和软线) / Wire Range (rigid and flexible) (mm ² /AWG)	0.5~1.5/ 28~16		
剥线长度 / Stripping length (mm)	3.50 N=02~24P		
使用温度范围 / Operating temperature (°C)	-40~+105		
符合RoHS环保要求 / Conform to RoHS	Yes		

SURFACE:


宁波三安电子科技有限公司
 Sanan Electrical Technology Co., Ltd

NAME: 15ESAK-3.5-XXP-1Y-00A(H)

MATERIAL:	
MAT NO.:	
STATUS:	
APPD:	
CHKD:	
DRT:	
DRAWING NO.:	
TYPE:	
SCALE:	
REV	
SHEET	
1/1	

公差 (General tolerances) (mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±1.20	±1.80	±2.50	±3.15	±4.00	±5.00

表面粗糙度	0.1/1.0
公差	±Z

SIZE: A4	mm	inch
TYPE:		
SCALE:		
REV		
SHEET		
1/1		